

APPLICATION

of

GREGG W. LEAVERTON

for

UNITED STATES LETTERS PATENT

on

FILTERING SYSTEM FOR A POOL OR SPA

Client ID/Matter No. AHEQU.66253

Sheets of Drawing Figures: 3

Express Mail Label No. EV 320200358 US

Attorneys
FULWIDER PATTON LEE & UTECHT, LLP
200 Oceangate, Suite 1550
Long Beach, CA 90802

FILTERING SYSTEM FOR A POOL OR SPA

Background of the Invention

[0001] This application is a continuation-in-part of U.S. Patent Application Serial No. 09/990,616, filed on November 21, 2001, now U.S. Patent No. _____, and continuation-in-part of U.S. Patent Application Serial No. 10/448,876 filed on May 30, 2003, now U.S. Patent No. _____.

[0002] 1. Field of the Invention:

[0003] The present invention relates to filter for liquids. More particularly, the present invention is directed to an internal filter for use in the water circulation systems of conventional pools or spas.

[0004] 2. General Background and State of the Art:

[0005] Filters of various configurations are known in the art for use in swimming pools, spas, and the like in order to remove solid particles and debris from the circulated water. Such filters are typically mounted in-line within the pool or spa circulation system and are configured with a liquid-permeable filter media such that when the circulation system is in operation, the water can be pulled through the filter and pumped back into the pool or spa, leaving the captured debris on the filter for subsequent removal.

[0006] The conventional cartridge filter as is known and used in the art is generally comprised of a cylindrical filter element having one or more layers or sheets of a porous material configured with a pore size to allow the passage of water while trapping and removing the solid particles from the water that are unable to pass through the pores. As the filter traps more and more solid particles, the pores in the filter media become clogged, inhibiting the flow of water through the pool or spa's circulation system and thereby decreasing performance and possibly even damaging the circulation pump. In an attempt to address these concerns, the cartridge filters known in the art typically employ relatively large sheets of the porous filter material that are pleated so as to provide an increased filter surface area, thus increasing the life and performance of the filter, while not increasing the filter's overall size. The filter material is maintained in its

cylindrical, pleated configuration by being mounted on a rigid cylindrical core and capped on each end by an annular end cap.

[0007] Though the conventional cartridge filter is in wide use, there are still several shortcomings with this filter type that have not yet been overcome. First, the flow rate through the cartridge filter is limited by the material and configuration of the pleats and the apertures in the rigid cylindrical core. Such flow rate is typically on the order of 100 gpm when the filter is new. Second, despite the overall increased surface area of the filter material achieved by the pleats, only so much of this surface area is truly usable, as the folds of the pleat are tight and are butted up against the cylindrical core. Moreover, as particles and debris become lodged between the pleats, the useful filter surface area that is lost is effectively doubled because the particles and debris clog pores on both adjacent surfaces of the pleat. Thus, cartridge filters become clogged and experience decreased flow rates relatively quickly. A third shortcoming of the cartridge filters known and used in the art is that they cannot be readily cleaned after becoming clogged. In the interest of increasing the total filter surface area, the pleats of the typical cartridge filter are numerous and densely configured about the filter's circumference. Thus, in order to remove the debris trapped deep within the pleat folds, high pressure reverse flow or meticulous debris removal using a vacuum or manual technique between each pleat is necessary. It is further recommended that the cartridge be soaked overnight in a cartridge cleaning solution and then be thoroughly cleaned a second time before being returned to use. Because of these inconveniences, some pool and spa owners simply use their cartridge filters until they become clogged and discard them, often prematurely, rather than bothering to clean them out. Moreover, because cartridge filters trap debris on the outside of the filter only, when the filter is removed from the pool or spa for cleaning or disposal, it is possible that the debris that is loose and easily removed will fall off the filter into the clean side of the circulation system rather than being permanently removed.

[0008] For these reasons, other pool and spa filters have been proposed in the art. Diatomaceous earth ("DE") filters house internal, parallel grids made of extremely fine mesh that is coated with DE, which is crushed, petrified bone that acts as an adhesive and traps particles and debris from the water as it is filtered through the layers of DE grids. These DE filters are relatively more expensive than comparable cartridge filters and may be subject to municipal or

environmental authority regulations pertaining to cleaning and disposal. Similarly, sand filters have also been proposed that essentially use a sand and gravel filter medium that mixes with the circulated water as it passes through the filter to pull out dirt and debris. However, the debris is not permanently captured by the sand filter medium and can eventually work its way through the filter and back into the pool or spa circulation system. It has been proposed that an additional solution be added to the sand to coagulate the particles and debris being filtered into larger clumps that can be more easily trapped by the sand filter medium. As a further maintenance step with sand filters, periodically, the sand itself is depleted from the filter and more sand of a specific type must be added. Sand filters, like the DE filters, are more costly than cartridge filters.

[0009] Bag-type filters for separation of unwanted solids from liquid process flows have also been employed in various industrial filtration applications in the interest of increasing flow rate and efficiency. To this end, filter assemblies having bag filters supported on rigid structures or stiffening frames and having elaborate sealing arrangements between the filter and the surrounding housing have been proposed. For example, U.S. Patent No. 4,769,052 to Kowalski is directed to a flexible fabric filter bag apparatus having multiple support surfaces. A double-walled, porous cylinder cooperates with a stretching frame to suspend and support the filter bag within a rigid cylindrical outer housing. An annular flange is provided in the housing's inner wall and is configured to sealingly engage a metal ring within the bag's open end when the bag, the double-walled cylinder, and the stretching frame are positioned inside the outer housing. A cover is installed over the open end of the outer housing to seal the filter and to force the stretching frame downwardly to draw the filter bag taut against the surfaces of the double-walled support cylinder.

[00010] U.S. Patent No. 5,910,247 to Outterside is directed to a similar filter bag system. Like the Kowalski filter apparatus, Outterside discloses essentially a double-walled filter support cylinder, consisting of an outer basket and an inner tubular member, a housing having a lid for sealing the filter, and a filter bag having a ring in its open end to sealingly engage a flange on the basket. Outterside further discloses specific dimensions for the filter bag which purportedly maximize the surface area without restricting the process flow rate.

[00011] Moreover, the Outterside system's supporting structures are configured to prevent collapse of the filter bag when the process flow is reversed to backwash and clean the filter without removing it. Hence, it is essential that the filter bag fit snugly and securely over the outer basket and inner tubular member. To this end, Outterside discloses that the filter body is smaller in diameter than the outside diameter of the tubular support member so that the filter must be stretched to fit over the tubular body and is retained thereon through a frictional fit.

[00012] See also W. L. Hopkins, U.S. Patent No. 2,865,511 which discloses a wire frame that holds a filter bag which encompasses such frame. The filter bag is disposed in a barrel. A liquid is pumped into the filter bag to remove solids which flow into the barrel. When the barrel is filled the liquid is released into a drum. Hopkins does not utilize a continuous flow system.

[00013] Therefore, the bag filters known and used in the prior art essentially entail a multi-walled support structure that may further include additional stretching or stiffening frames, a filter bag that is secured on the support structure and shaped by the alternative frames, and a filter housing, or vessel, that contains the filter bag assembly and provides for a positive seal between the "dirty" and "clean" side of the filter along a ring integral to the bag's open end. Based on the configuration and number of components in these prior art industrial bag-type filters, it follows that such filters are not well-suited for use in spas because of their complex design and inherent relatively high cost. Furthermore, the housing, which plays a critical role in the function and performance of the prior art bag-type filters, is particularly ill-suited for use in a spa's circulation system because the conventional spa's filter-receiving cavity cannot accommodate the housing, and the housing itself, having only one small inlet strategically positioned above the location where the filter is sealed within the housing, would likely perform poorly under the changing water levels and other conditions of a pool or spa during use.

[00014] Thus, there exists a need for an inexpensive, convenient, and functionally efficient filter for use in spas and the like that is both easily reusable and disposable.

Invention Summary

[00015] The present invention is directed to an internal spa filter including a filter body and a complementary filter bag having a sheath which encompasses the exterior of the filter body and

an internal pocket which extends into the filter body. The filter body is configured to be installed within a spa's water circulation system in order to filter particles and debris out of the water. As the spa water is circulated, through the filter body a vortex effect is created within the filter bag pocket trapping debris therein for later removal without the risk of the debris falling off the filter and back into the spa water. The configuration and materials of the spa filter of the present invention, as compared to the prior art filters, provide for much higher flow rates through the filter, further enhancing both the performance and life of the pump of the spa circulation system. Moreover, the spa filter of the present invention is relatively inexpensive to manufacture, whereby, after prolonged use, the filter bag itself may be either readily cleaned and reused or alternatively simply discarded.

[00016] The filter body of the spa filter of the present invention is defined by a cylinder having a spa water opening at its inlet end and a spa water discharge orifice at its opposite end. Throughout the filter body's cylindrical wall is formed a pattern of auxiliary spa water inlet openings. The inlet and auxiliary openings permit the passage of the circulated spa water from the outside of the filter body to the inside thereof. The sheath of the filter bag is joined to the pocket thereof along a circumferential inseam. Accordingly, when the bag is placed about the filter body, the closed end of the pocket is inserted within the filter body's open end while the sheath encompasses the outside surface of the filter body's cylindrical wall, with the inseam of the filter bag positioned substantially along the inlet edge of the cylindrical wall's inlet end to maintain the position of the filter bag on the supporting filter body. The pocket extends towards the discharge end of the filter body.

[00017] One embodiment of the filter body utilizes a cylinder, the sides of which are formed with a pattern of round through-hole openings preferably having a nominal diameter of 0.60". For a cylinder having an outside diameter of approximately 5-1/2" and a length of approximately 8", sixteen such holes are radially-spaced apart in each of six parallel, circumferential rows in the wall to yield a total of ninety-six through holes generally spaced uniformly throughout the wall. In an alternative filter body embodiment, a mesh-type pattern is formed in the cylinder sidewall having a pattern of small, square apertures throughout the wall arranged in spaced-apart relationship about parallel circumferential rows substantially throughout the wall. Because the square apertures are relatively smaller than the through-hole apertures of the first embodiment,

for the same overall dimensions of the wall, the number of square apertures and the number of rows are significantly increased, yielding a total of more than two-thousand square apertures. A third embodiment of the filter body of the present invention has lengthwise axially extending slots formed about its circumference.

[00018] In each embodiment of the filter body, the body includes an open inlet end about which the filter bag sheath is draped and an opposite rear closed discharge end formed by a rear wall integral with the rear end of the filter body and generally normal to the axis of the filter body. A central circular discharge orifice is provided in the wall for discharge of the flow of the spa water entering the filter body through the filter bag. A length of tubing extends from the discharge orifice normal to the rear wall and projecting axially away from the filter body. The tubing is configured with external threads for threadably engaging piping of the spa's circulation system. Preferably, the filter body will be positioned vertically within a filter-receiving bay of the spa with the inlet end of the cylinder disposed above the discharge end thereof so that water from the tub of the spa is drawn downwardly through the filter body to the suction end of the spa's pump. The aforescribed filter is also described hereinafter as being utilized to filter spa or swimming pool water being pumped through a closed filtering tank in order to remove debris from such water. The filter body may be constructed of a thermoplastic material such as polyethylene (PE), polypropylene (PP), polyvinyl chloride (PVC), or acrylonitrile butadiene styrene (ABS). These materials are readily available, are relatively inexpensive, and are easily processed using injection molding and finishing techniques known in the art.

[00019] The filter bag of the present invention includes a support ring at the juncture of the sheath and pocket along a circumferential inseam formed by looping the upper end of the pocket over the upper end of the sheath to form a loop or circumferential cavity. The support ring preferably has a nominal diameter substantially equivalent to the nominal diameter of the filter body so as to be positioned adjacent the upper end of the filter body when the filter bag is placed on the filter body, thereby maintaining the filter bag in position and keeping the pocket open during use. To this end, the support ring is to be constructed of any suitable rigid or semi-rigid material such as a thermoplastic material or stainless steel. To maintain the position of the support ring within the circumferential cavity and to secure the inseam, stitching, welding, stapling or other fabric attachment means known in the art are employed.

[00020] A removal handle spans the open upper end of the filter bag pocket and is attached at two opposite locations. The handle may be stitched, welded, or otherwise joined to the filter bag using any attaching means known in the art, but is preferably attached within the inseam itself. The length of the handle is sufficient to loosely span the pocket opening, so that the handle may droop within the pocket when not in use and may be pulled up for convenient access when the handle is to be grasped to remove the filter bag from the filter body.

[00021] The filter bag of the present invention may be constructed of a durable, porous, fibrous material known in the art for use in various filtration applications. Though many types of fabrics may be used in fluid filtration to effectively remove debris and particulate matter while allowing the fluid itself to pass through the filter media, in a preferred embodiment, the material selected will have a porosity rating of 40 to 50 microns and have a weight on the order of 12 oz/yd². Examples of suitable materials include polypropylene (PP), polyethylene (PE), polyester felt, or fiberglass. The handle may be made of the same material as the sheath and the pocket or may be made of a conventional cotton and polyester textile material.

[00022] In operation, after the sheath of the filter bag has been removably positioned in covering relationship over the filter body with the bag pocket extending into the filter body, the internal spa filter of the present invention is ready for use and is installed within the filter-receiving bay or the closed filtering tank of a conventional spa with the filter in direct communication with the spa's circulation system on the suction side of the pump. Once the spa tub is filled with water and the circulation system is operated, the water is drawn through the filter by the pump. Because the inlet opening of the filter bag, approximately 5-½" diameter, is relatively larger than the discharge orifice at the closed end of the filter body, which is typically on the order of 1-½", this difference in area will naturally create a vortex tending to draw the water down through the filter pocket, pulling larger debris into the pocket and trapping it there for later removal. The vortex action and the resulting strong suction of water through the filter also creates a vacuum pressure on the inside of the filter that serves to pull the filter bag's sheath tightly against the exterior of the filter body, thus effectively creating a tight fit between the sheath and the filter body which causes all water being pulled through the filter to pass through the filter bag.

[00023] The porosity of the filter bag material, the configuration of the open pocket, and the vortex effect cooperate to provide for higher flow rates through the filter (on the order of about 150 gallons per minute) as compared to conventional prior art spa filters. This increased flow rate translates to enhanced performance of the spa in terms of the relaxation and therapeutic benefits to the user and the life of the circulation pump.

[00024] When the filter bag of the present invention has become sufficiently dirty that it should be cleaned or replaced, the spa's circulation system is shut down and the filter bag is simply lifted out of the filter body by grasping the handle. The debris trapped by the filter during use will remain within the inside pocket, thereby not contaminating the spa water as the filter bag is removed from the filter-receiving bay or filtering tank. If the filter bag is removed from the bay or tank to be cleaned for reuse, the bag is dumped or rinsed out to remove all debris that has been trapped or alternatively may be washed or laundered in a conventional washing machine and dryer to more thoroughly clean and sanitize the bag. If it is preferred that the filter bag be replaced rather than being cleaned, the used filter bag may be simply discarded and a new bag put into the filter body. Because the materials and construction methods employed in producing the filter of the present invention are relatively inexpensive, disposing of the filter bag is both a convenient and economical it cleaning the bag.

[00025] Other features and advantages of the invention will become apparent from the following detailed description, taken in conjunction with the accompanying drawings, which illustrate, by way of example, the features of the invention

Brief Description of the Drawings

[00026] FIG. 1 is a cut-away perspective view of an internal spa filter embodying the present invention showing the filter bag positioned on the cylindrical filter body;

[00027] FIG. 2 is a perspective view of the filter body shown in FIG. 1;

[00028] FIG. 3 is a broken perspective view of the discharge end of the filter body shown in FIG. 1;

[00029] FIG. 4 is a perspective view of a first alternative embodiment of the filter body;

[00030] FIG. 5 is a perspective view of a second alternative embodiment of the filter body;

[00031] FIG. 6 is a cut-away perspective view of the filter bag shown in FIG. 1;

[00032] FIG. 7 is a cut-away perspective view of the filter bag positioned upon the filter body of FIGS. 1, 2, and 3;

[00033] FIG. 8 is a vertical sectional view taken along line 8-8 of FIG. 7;

[00034] FIG. 9 is a perspective view of an internal spa filter of the present invention installed within a spa's filter-receiving bay.

[00035] FIG. 10 is a cut-away perspective view of said internal spa filter during operation of the spa's water circulation system;

[00036] FIG. 11 is a vertical sectional view showing the operation of a vortex created during operation of the spa's water circulation system;

[00037] FIG. 12 is a broken sectional view showing a filter bag being removed from a spa's filter-receiving bay;

[00038] FIG. 13 is a perspective view of a closed filtering tank for a filter of the type shown in Figs. 1-12;

[00039] FIG. 14 is a top plan view of the filtering tank of Fig. 13;

[00040] FIG. 15 is a vertically exploded view of the tank of Figs. 13 and 14 wherein is removably disposed a filter of the type described in Figs. 1-12;

[00041] FIG. 16 is a vertical sectional view taken in enlarged scale along line 16-16 of Fig. 14;

[00042] FIG. 17 is a horizontal sectional view taken along lines 17-17 of Fig. 16;

[00043] FIG. 18 is a horizontal sectional view taken along lines 18-18 of Fig. 16; and

[00044] FIGS. 19 and 20 are diagrammatic views showing how the filtering tank of Figs. 13, 14 and 15 is operatively positioned in a water circulation system for a pool or spa;

Detailed Description of the Preferred Embodiments

[00045] While the specification describes particular embodiments of the present invention, those of ordinary skill can devise variations of the present invention without departing from the inventive concept.

[00046] As shown in the drawings for purpose of illustration, an internal spa filter of the present invention utilizes a filter bag removably disposed upon a cylindrical filter body and configured to be installed within a spa's circulation system in order to filter particles and debris out of the spa water. While the spa filter embodying the present invention is described and depicted as being used in a conventional spa, it will be appreciated that the invention can also be used in conjunction with above- and below-ground swimming pools, hot tubs, Jacuzzis, or with any other system involving recirculated water that is to be filtered.

[00047] More particularly, referring to **FIG. 1**, a preferred embodiment of an internal spa filter **F** of the present invention includes a cylindrical filter body **FB** and a filter bag **B** having a cylindrical sheath **20** and a pocket **22** that extends concentrically inwardly and downwardly from the inlet end of the sheath. The upper end of the cylinder **24** of the filter body is open to define an inlet opening **26** for spa water drawn downwardly through the cylinder by the pump **28** of the spa's water circulation system (**FIG. 9**). The lower end of the cylinder **24** is closed by a bottom wall **30** centrally formed with a discharge orifice **32** (**FIG. 3**). The bottom of filter bag pocket is generally horizontal and spaced above the discharge orifice **32**. The sidewalls **34** of cylinder **24** are formed with auxiliary spa water openings in the form of holes **36** that admit spa water that is drawn into cylinder **24** through sheath **20** of the filter bag. In the use of the internal spa filter **F** all spa water being circulated through the filter will pass through and be filtered by the filter bag. Moreover, since the discharge orifice **32** is smaller in area than the inlet opening **26** and the bottom of filter bag pocket **22** is spaced above the discharge orifice **32**. A vortex **37** may be created during circulation of the spa water which traps debris in the pocket **22** for later removal as indicated by the arrows in (**FIGS. 10 and 11**). A handle **38** is provided on the filter bag to permit the bag to be conveniently lifted from the filter body for cleaning or replacement.

[00048] A short tube **40** coaxial with the discharge opening **32** extends downwardly away from cylinder end wall **30** to form a water connection means between discharge orifice and the suction

end of pump **28** (**FIG. 9**) of the spa's water circulation system. The tube **40** is formed with threads **42** for threadably engaging piping **44** connected to pump **28**. A preferred conventional thread size is 1.50 mps with a major thread diameter of approximately 1.90". This thread configuration accommodates a bore **64** through the tubing **60**, and thus a circular opening size, of about 1-1/2".

[00049] With continued reference to **FIG. 2**, the holes **66** are round and preferably have a nominal diameter of about 0.60". In this same embodiment, sixteen such holes are radially-spaced apart in each of six parallel, circumferential rows in the cylinder **24** to yield a total of ninety-six through holes generally spread uniformly throughout the wall of the cylinder sidewall. It will be appreciated that the cylinder may be of a variety of lengths and diameters and that as the overall dimensions of the cylinder change, the pattern of holes may change accordingly in order to maintain a generally uniform distribution of the holes throughout the wall of the cylinder. In the embodiment shown in **FIG. 2**, the cylinder is configured with a nominal outside diameter of 5-1/2" and a length of 8", as is typical in the art of spa filters, permitting a filter of the present invention to be capable of use with the majority of spas currently on the market.

[00050] The filter body **FB** may be constructed from a number of different water-resistant materials known in the art. A preferred material is a thermoplastic such as polyethylene (PE), polypropylene (PP), polyvinyl chloride (PVC), or acrylonitrile butadiene styrene (ABS). It will be appreciated that these materials are readily available, are relatively inexpensive, and are easily processed using injection molding and finished techniques known in the art. Because the filter body is configured to be one integral unit, the injection molding process is both effective and efficient in this application. In an alternative embodiment, the threaded tubing **40** may be formed separately through a molding or machining operation and bonded or welded to the filter body in a secondary operation.

[00051] Referring now to **FIG. 4**, an alternative embodiment of filter body **FB'** of the present invention, utilizes a cylinder **46** having a pattern of auxiliary water openings in the form of small apertures **48** formed throughout the wall of the cylinder to define a mesh-type construction. Preferably the apertures will be square shaped. Apertures **48** are arranged in spaced-apart relationship about parallel circumferential rows substantially throughout the wall of cylinder **24'**,

but, because the apertures are relatively smaller than the through-holes 36, the number of apertures and the number of rows are significantly increased. Thus, in one such embodiment, a cylinder 24' having a 5-½" nominal outside diameter and an 8" length is configured with thirty-three rows of sixty-nine 1/8" apertures each and, thus, has a total of 2,277 apertures in the tubular wall. It will be appreciated that though the number of apertures is significantly increased over the number of through-holes in the filter body **FB** of **FIG. 2**, the total area for throughput of fluid from the outside of the filter body to the inside is not necessarily increased commensurately, but is, however, increased significantly. For example, in the exemplary embodiments disclosed, the total throughput area for the ninety-six through-holes (**FIG. 2**) is 27.1 in² as compared to a total throughput area for the 2,277 apertures (**FIG. 3**) of 35.6 in². As with the filter body **FB**, the mesh filter body **FB'** includes a flat wall 30' formed with a discharge orifice 32'. A central, externally-threaded tube 40' extends from wall 30' for engaging the spa's circulation system. The front of cylinder 24' defines a spa water inlet opening 26'.

[00052] With reference now to **FIG. 4**, there is shown a third embodiment of a filter body **FB''** of the present invention. Filter body **FB'** utilizes a cylinder 24" having auxiliary spa water openings in the form of lengthwise rectangular slots 52 formed about its sidewall. Slots 52 are defined by lengthwise, radially spaced-apart ribs 54 which extend along the wall of the cylinder. As with both the filter body **FB** and aforescribed mesh filter body **FB'**, the ribbed filter body **FB''** includes an inlet opening 26' and an integral bottom wall 30". Bottom wall 30" is formed with a central circular discharge orifice 32" from which extends an integral threaded tubing 56 for engaging piping 40" of the circulation system of a spa.

[00053] In the embodiment of the ribbed filter body **FB''**, shown in **FIG. 5**, the nominal outside diameter of the cylinder is approximately 5-½" and the overall length is approximately 8", just as for the aforescribed filter body **FB** and the mesh filter body **FB'**. Twelve lengthwise ribs 54 may be spaced evenly about the circumference of the filter body at substantially 30-degree intervals, with each rib having a radial width of about 0.125". In this embodiment, the total throughput area for the twelve slots 52 is about 110 in², a significant increase over the throughput areas for both the filter bodies **FB** and **FB'**. The effect of the throughput surface areas of the various embodiments on the performance of the internal spa filter under use is explained below.

[00054] Referring now to **FIGS. 6, 7, and 8**, the filter bag **F** of the present invention includes a generally tubular outside sheath **20** attached to a generally conical inside pocket **22** along a circumferential inseam **60**. The sheath has an upper inlet end **62** and a lower, discharge end **64**, while the pocket has an upper end **66** continuous with the upper end of the sheath, and a lower end **68**. The inseam **60** is formed by the union of the sheath and pocket along their respective upper ends. The lower end **68** of the pocket is stitched, welded, or otherwise formed closed to provide a radiused tip at the bottom of the generally conically shaped cavity **70**.

[00055] Preferably in the filter bag **F** of the present invention, both the sheath **20** and the pocket **22** are constructed of a durable, porous, fibrous material known in the art for use in various filtration applications. It will be appreciated that many types of fabrics may be used in fluid filtration to effectively remove debris and particulate matter while allowing the fluid itself to freely pass through the filter media. In a preferred embodiment, the material selected will have a porosity rating of about 40 to 50 microns. Such a material would typically have a weight on the order of 12 oz/yd². Examples of suitable materials include polypropylene (PP), polyethylene (PE), polyester felt, or fiberglass. Polypropylene is preferred, particularly for its longevity as compared to other similar fabrics.

[00056] The arcuate shaped handle **38** spans the open upper end **61** of the pocket **22** and is attached to the filter bag **20** at the inseam **60**. Opposite first and second handle ends are attached at the inseam at approximately 180 degrees apart, on opposite sides of the sheath and pocket. The handle may be stitched, welded, or otherwise joined to the filter bag using any attaching means known in the art. The length of the handle is to be sufficient to loosely span the pocket opening, so that the handle may droop within the pocket when not in use and may be pulled up for convenient access when the handle is to be grasped to remove the filter bag from the filter body. The handle may be made of the same material as the sheath and the pocket or may be made of a conventional cotton and polyester textile material known for its durability, minimal shrinkage and wide range of uses.

[00057] Referring now to **FIGS. 7 and 8**, the inseam **60** is formed by looping the upper edge of the pocket over the upper end of the sheath so that the upper end of the pocket is substantially turned back on itself 180 degrees to contact both the inside and outside surfaces of the upper

sheath end. In a preferred embodiment, sufficient clearance is left between the upper sheath end and the looped portion of the upper pocket end to form a loop or circumferential cavity **70** about the inseam **60**. Disposed within the circumferential cavity is a support ring **72** of a circular cross-section. The support ring preferably has a nominal diameter substantially equivalent to the nominal diameter of the filter body so as to seat on the top end of the filter body when the filter bag is placed on the filter body, thereby maintaining the filter bag in position on the filter body and keeping the upper end of the pocket open during use. The support ring **72** is constructed of any suitable rigid or semi-rigid material such as a thermoplastic or stainless steel. Beyond the mechanical attributes of the support ring, the selected material must be water and corrosion-resistant. To maintain the position of the support ring **72** within the circumferential cavity **70** and to secure the inseam **60**, a double-stitch **74** may be employed. As shown in **FIG. 8**, the stitch is to pass below the circumferential cavity through the outside, looped portion of the upper pocket end, through the upper sheath end, and then through the inside portion of the upper pocket end to hold the inseam together. It will be appreciated that the inseam may also be secured by other stitch configurations, welding, stapling or other fabric attachment means known in the art.

[00058] Referring now to **FIG. 1**, in preparing an internal spa filter **F** of the present invention for use, the filter bag **FB** is positioned on the filter body by sliding the lower sheath end **30** over the top end of the filter body until the top inseam **60** is substantially aligned with the top end of the filter body. In order for the filter bag to have a loose but functional fit on the filter body, the inside diameter of the sheath **22** is to be at least 0.100" larger than the outside diameter of the filter body, but no more than 0.300" larger, which would create a clearance of at least 0.050" between the filter bag and the filter body about the circumference. Thus, for example, in the embodiment of the filter body having a nominal outside diameter of 5-½", the inside diameter of the filter bag sheath would be at least 5.600". In order for the filter bag to be in covering relationship about the outside surface of the filter body, the overall axial length of the sheath is preferably substantially equivalent to the axial length of the filter body's cylinder. In this way, when the filter bag is advanced as far as possible along the filter body and the inseam adjacent filter body's top end, the discharge end **64** of the sheath will be substantially adjacent the filter body's bottom end.

[00059] With continued reference to **FIG. 11**, at the same time that the filter bag's sheath **20** is slidably advanced along the outside surface of the filter body cylinder **24**, the pocket **22** is inserted through the filter body's inlet opening **26**. The overall length of the pocket is preferably configured such that when the filter bag is operationally positioned on the filter body, the pocket's bottom end is substantially adjacent to and above the discharge orifice **32**. In this way, the available surface area of the filter bag **20** for filtration is maximized without risking occlusion of the opening at the filter body's discharge end.

[00060] Referring now to **Figs. 13-22**, there is shown a closed filtering tank **T** system provided with one of the filters **F** described hereinbefore and shown in **Figs. 1-12** of the drawings.

[00061] As shown particularly in **Fig. 16**, filtering tank **T** includes a vertically extending cylinder **100** which extends upwardly from a manifold **102**. The open upper end of the cylinder **100** is provided with a cover **104**. Seal ring **106** is interposed between the upper end of the cylinder and the cover. The upper end of the tank is provided with threads **108** complimentary to internal threads **110** of the cover **104**. The manifold **102** includes a mounting neck **112** that is threadably engaged with the tube **40** of the filter body **FB** of filter **F** to support filter **F** within filtering tank **T**. The filter body **FB** of filter **F** releasably receives a filter bag **FB** of the type described in detail hereinbefore. Preferably an O-ring **112** resiliently encircles the upper portion of filter bag **FB** and exerts a radially inwardly directed force against the exterior of the filter bag to releasably anchor the filter bag to the upper portion of the filter body so as to prevent inadvertent upward motion of the filter bag off the filter body **FB** during circulation of water through the interior of tank **T**. The upper portion of filter bag **FB** is provided with a handle **38** as described hereinbefore. The tank manifold **102** is formed with a horizontal outlet passage **114** and is also formed with a horizontal inlet passage **118**.

[00062] In the operation of the form of the invention shown in **Figs. 13-20**, water from the pool or spa is circulated by the pump **P** through the filtering tank **T**, such water flowing upwardly under pressure from inlet passage **118** through the interior of the tank into the upper end of the filter body **FB**. Such water then flowing downwardly through pocket **22** of the filter bag **B** and concurrently radially inwardly through the sheath **20** of the filter bag and auxiliary water openings **36** of the filter body, as indicated by the directional arrows in **Fig. 16 and 18**. All of

the water then flows downwardly through discharge orifice 32 and filter body tube 40 into the outlet passage 114 of the tank manifold. Depending upon the rate and pressure of the water flowing into tank T a vortex action may be introduced within the filter bag pocket 22 in the manner described hereinbefore with respect to **Figs. 1-12**.

[00063] Referring now to **Fig. 19**, outlet passage 114 is connected to return piping 120 in communication with water contained in the pool or spa. Inlet passage 118 is connected to the discharge side of a conventional pump P by supply piping 122. The suction side of pump P is connected by a second length of supply piping 123 to a conventional skimmer box or the like 124 that is open to water from the pool or spa in a manner known to those skilled in the art.

[00064] The pump P, piping 120, 122 and 123, filtering tank T and skimmer box 124 form a water circulation system for the water in the pool or spa which provide effective filtration for the water in the pool or spa. When the filter bag B has become dirty and is to be cleaned and replaced, the pump P is shut down and the cover 104 screwed off of the top of the tank cylinder 100. The filter bag B may then be lifted out of the filter body FB by simply grasping the handle 38 and pulling the bag up and out of the filter body. Debris contained within the filter bag pocket and the interior of the tank T is then removed and a new or a clean filter bag is positioned over the filter body.

[00065] Referring now to **Fig. 20**, there is shown a second system having outlet piping 126 and 127 between which is positioned between outlet passage 114 and the interior of tank T, with pump P being interposed between such piping 126 and 127. Inlet passage 118 is shown connected to supply piping 128 to skimmer box 130.

[00066] While embodiments of the invention have been illustrated and described, it will be apparent that various modifications can be made without departing from the spirit and scope of the invention. Accordingly, it is not intended that the invention be limited, except as by the appended claims.